

PRO WELD

INTERNATIONAL

CD-212

CAPACITOR DISCHARGE STUD WELDER

DESCRIPTION

The CD-212 is a state-of-the-art solid state capacitor discharge stud/pin welder. Its lightweight design increases portability but with the power to weld 1/4" diameter flanged studs.

The extremely short weld time of capacitor discharge process allows studs to be welded to material as thin as .015 without burn-through.

The unit is capable of welding mild steel, stainless and aluminum studs.

SPECIFICATIONS

DIMENSIONS: 8-1/2"H x 9"W x 11-3/4"D
 WEIGHT: 26 LBS.
 MODE: CONTACT
 STUD RANGE: 14 GA.-1/4"
 WELD RATE: 12 STUDS/ MIN.
 CAPACITANCE: 66,000 MFD
 INPUT POWER: 110 VAC,60 HZ
 20 AMPS
 CHARGE RANGE: 45-200 VDC

COMPONENTS

ITEM	DESCRIPTION:	PART NO.
POWER SUPPLY	110 VAC 60 HZ	200-0015
POWER SUPPLY	GAP	200-0019
WELD GUN	L.D. B-COLLET	300-0100
WELD GUN	L.D. TAPER BASE	300-0101
WELD GUN	L.D. PRECISION	300-0102
WELD GUN	GAP	300-0700
WELD GUN	BANTAM C-2	300-0301
GROUND CABLE	#4 x 15' AND CLAMP	125-0100



FEATURES

- * Designed and built in U.S.A.
- * Light Weight Aluminum Cabinet
- * Powder Coated
- * Safety Fault Shut Down
- * Recessed Control Panel
- * Circuit Breaker Protection
- * 3 Year Warranty on PCB

DISTRIBUTED BY